

Reducing Energy Cost

Optimizing Performance through Energy Efficiency Best Practices

Dale Sartor, Staff Engineer, Lawrence Berkeley National Laboratory
Rachel Shepherd, DOE Federal Energy Management Program, Data Center Program Lead

Version 050320






Agenda


- DOE's Federal Energy Management Program
- Challenges and Opportunities
 - DOE's data center (HPC) growth
 - Best practice benchmarking
 - A continuous improvement process
 - Efficiency best practices to optimize and reduce cost
- LBNL's Center of Expertise Technical Assistance
 & Resources

Next Month

- Team Approach to Energy and Cost Saving Opportunities
 - LBNL's continuous improvement process save big \$
- Tools and Resources

Federal Government's Potential







\$151 *billion* of deferred maintenance and repairs is required to bring government owned property, and equipment to an acceptable condition.


Between **\$9** *billion* and **\$15** *billion* of potential self-financing efficiency measures exist in Federal buildings.



Federal Energy Management Program

Providing strategic energy management for agencies to become resilient, efficient and secure in support of Administration priorities for American Energy Dominance, Increased Government Accountability and Development of a Future-Focused Workforce.





Performance Contracting Delivers Results

FY 2018 DOE ESPC IDIQ

\$809 Million Record Investment by Federal Agencies in Support of Increased Resilience



A LEADERSHIP: Government Efficiency

FOCUS: Retrofits for Resilience

10 AGENCIES

Environmental Protection Agency Federal Aviation Administration

Federal Bureau of Prisons

General Services Administration

National Aeronautics and Space Administration

U.S. Air Force

U.S. Department of Energy

U.S. Navy

U.S. Office of Personnel Management

U.S. Veterans Affairs

Replacing Aged Equipment with **Highly Efficient Equipment**

Incorporating Combined Heat & Power, Microgrids, & Battery Storage to Address \$165 Billion of Deferred Maintenance



INVESTMENTS: Strengthen Infrastructure



Highly Efficient Equipment Enables Almost \$1.7 Billion in Energy & **Water Savings**

Good Jobs in Engineering, Construction, & Manufacturing

6,475 Job Years Created

Webinar: Opportunities For ESPCs In Data Centers Thursday, May 21 1:00 - 2:30 PM EST

https://www.wbdg.org/continuing-education/fempcourses/femplw05212020

FEMP's Data Center Program



FEMP's Data Center program assists federal agencies and other organizations with optimizing the design and operation of data centers. design and operation of energy and water systems in data centers to enhance agency's mission.

Assistance

- Project and technical assistance from the <u>Center of Expertise</u> for Energy Efficiency in Data Center
- Support agencies in meeting OMB's Data Center Optimization Initiative requirements

Tools

- <u>Data Center Profiler</u>
 (<u>DC Pro) Tools</u>,
 including PUE
 Estimator
- Air Management Tools
- Energy Assessment Worksheets

Key Resources

- <u>Better Buildings Data</u> <u>Center Challenge and</u> <u>Accelerator</u>
- Small Data Centers,
 Big Energy Savings: An
 Introduction for
 Owners and Operators
- <u>Data Center Master</u>
 <u>List of Energy</u>
 <u>Efficiency Actions</u>

Training

- Better Buildings webinar series
- Ten on-demand FEMP data center trainings
- <u>Center of Expertise</u>
 <u>Webinars</u>
- <u>Data Center Energy</u>
 <u>Practitioner</u> Trainings

Data Center Energy

Data centers are energy intensive facilities

- 10 to 100+ times more energy intensive than an office
- Server racks now designed for more than 30 kW
- Surging demand for data processing and storage
- 1.8% of US electricity consumption
- Power and cooling constraints in existing facilities
- Perverse incentives
 - ✓ IT and facilities costs separate

Potential Benefits of Energy Efficiency


- 20-40% savings & high ROI typical
- Aggressive strategies can yield 50+% savings
- Extend life and capacity of infrastructures
- Increased resiliency



Projected Energy at 8 DOE National Labs


DOE sites with new HPCs, 2003-2028

Potential Data Center Impact on Energy Consumption




Please note the energy consumption data in this chart is for sites with planned/new large data centers/HPCs only: ANL, LANL, LBL, LLNL, NREL, NETL, ORNL and SNL. Information is based on FY 2019 reported data and does not reflect current status. Increase due to HPC is in dark blue.

Power and Efficiency of Top Supercomputer




Efficiency




First Step: Benchmark Energy Performance

- Compare to peers
 - Wide variation
- Identify best practices
- ID opportunities
- Track performance
 - Can't manage what isn't measured
- The relative percentage of energy actually doing computing varies
- High level Metric: PUE



Power Utilization Effectiveness (PUE) = Total Power/IT Power

No Silver Bullet - Just Continuous Improvement



Franklin Air-cooled Cray XT4 0.27 PF 2007

Hopper

Hybrid w/ chillers

Cray XE6 1.05 PF 2010

Edison

Hybrid w/ full-time economizers

Cray XC30 1.26 PF 2013

Cori

Hybrid w/ full-time economizers

Cray XC40 14.0 PF 2015

Energy Efficiency

Optimization Project

2017 - ongoing


Edison Retirement

May 2019

Oakland


Berkeley


Data Center Energy Efficiency Opportunities



IT Load/Computing Operations


- Increase Computations/Watt
- IT Equipment Efficiency
 - Use ENERGY STAR
 - Use efficient power supplies and optimize redundancy
 - Enable power management (e.g., sleep mode)
- Virtualize for higher utilization
- Reducing IT load has a multiplier effect
 - Savings in infrastructure energy depends on PUE






Enhance Monitoring: Using IT to Save Energy in IT

- Operators lack visibility into data center environment
- Provide same level of monitoring and visualization of the physical space as we have for the IT environment
- Measure and track performance
- Spot problems early
- Example: 800 pt system at LBNL



LBNL Wireless Monitoring System


source: SynapSense



Real-time PUE Display

Cooling with Better Air Management

- Typically, more air circulated than required
- Air mixing and short circuiting leads to:
 - Low supply temperature
 - Low Delta T



Raised Floor


70-80° vs. 45-55°

Isolate Cold and Hot Aisles

- Use hot and cold aisles
- Improve isolation of hot and cold aisles
 - Reduce fan energy
 - Improve air-conditioning efficiency
 - Increase cooling capacity

Environmental Conditions: Safer Limits and Guidelines

CPU, GPU & Memory, represent ~75-90% of heat load ...




GPUs ~75C (167F)


Memory ~85C (185F)

So why do we need jackets in data centers?

ASHRAE Thermal Guidelines



- Provides common understanding between IT and facility staff
- Provides wider humidity ranges
- Recommends temperature range up to 80.6° F with "allowable" much higher, up to 113° F.




Humidity Control & Cost

	Visalia Probe			CRAC Unit Panel				
	Temp	RH	Tdp	Temp	RH	Tdp	Mode	
AC 005	84.0	27.5	47.0	76	32.0	44.1	Cooling	
AC 006	81.8	28.5	46.1	55	51.0	37.2	Cooling & Dehumidification	
AC 007	72.8	38.5	46.1	70	47.0	48.9	Cooling	
AC 008	80.0	31.5	47.2	74	43.0	50.2	Cooling & Humidification	
AC 010	77.5	32.8	46.1	68	45.0	45.9	Cooling	
AC 011	78.9	31.4	46.1	70	43.0	46.6	Cooling & Humidification	
Min	72.8	27.5	46.1	55.0	32.0	37.2		
Max	84.0	38.5	47.2	76.0	51.0	50.2		
Avg	79.2	31.7	46.4	68.8	43.5	45.5		

Eliminate inadvertent dehumidification

- Computer load is sensible only
- Use ASHRAE allowable RH and temperature
 - Many manufacturers allow even wider humidity range
- Eliminate equipment fighting
 - Coordinate controls
 - Turn off



Use Free Cooling


Cooling without Compressors

- Water-side Economizers
- Outside-Air Economizers




Let's get rid of chillers in data centers

Data Center Opportunity: Getting Liquid Closer




Power Conversion and Distribution



Power Conversion and Distribution

- Increase voltage distribution
- Buy high-efficiency, modular (scalable), UPS
- Use efficient redundancy strategies
 - Different strategies have different energy penalties (e.g. 2N vs. N+1)
 - Redundancy in electrical distribution puts you down the efficiency curve
 - Consider redundancy in the network rather than in the data center

UPS Efficiency



Best Practices Summary

- Identify IT Equipment and Software Opportunities
- 2. Use IT to Monitor and Control IT (+ M&V)
- 3. Manage Airflow
- 4. Optimize Environmental Conditions, e.g. Humidity
- 5. Evaluate Cooling Options including Free Cooling and Liquid Cooling
- 6. Improve Electrical Efficiency Power Conversion and Distribution

Overcoming Barriers to Success

Barriers to success

- Organizational Inertia, conflicting goals, and risk aversion
- Lack of funding
- Lack of manpower / expertise

FEMP can help overcome these barriers

- Technical Resources and Assistance
- ESPC and UESC (attend upcoming ESPC webinar)

Get IT and Facilities people talking and working together as a <u>team</u>!!!

Data Center Services for Federal Agencies

FEMP provides the following data center services through the Center of Expertise for Energy Efficiency in Data Centers:

- Project Assistance
- Tools
- Resources
- Training



https://datacenters.lbl.gov/

Visit the FEMP training website for upcoming data center webinars: https://www4.eere.energy.gov/femp/training/

FEMP is Ready to Help!



Dale Sartor, P.E.
Lawrence Berkeley National Laboratory
MS 90-3111
University of California
Berkeley, CA 94720

DASartor@LBL.gov (510) 486-5988 http://datacenters.lbl.gov/





Rachel Shepherd
Data Center Program Lead
U.S. Department of Energy
Federal Energy Management Program

Rachel.shepherd@ee.doe.gov